



MURSATT CHEMICALS LIMITED
11 REGALCREST COURT
WOODBIDGE, ONTARIO, CANADA, L4L 8P3
(905)-850-8444

PRODUCT: VINYL PLUS

CODE: MUR0017

SECTION 01: IDENTIFICATION

PRODUCT CODE..... MUR0017
 PRODUCT IDENTIFIER..... VINYL PLUS
 OTHER MEANS OF IDENTIFICATION..... N.AV.
 RECOMMENDED USE AND N.AV.
 RESTRICTIONS ON USE
 SUPPLIER IDENTIFIER..... MURSATT CHEMICALS LIMITED
 11 REGALCREST COURT
 WOODBRIDGE, ONTARIO
 CANADA
 L4L 8P3
 EMERGENCY PHONE NO..... CANUTEC (613)-996-6666.

SECTION 02: HAZARD IDENTIFICATION



HAZARD CLASSIFICATION..... FLAMMABLE LIQUIDS - CATEGORY 4. CORROSIVE TO METALS - CATEGORY 1 .
 OXIDIZING LIQUIDS — CATEGORY 3. ACUTE TOXICITY (ORAL) - CATEGORY 4. SKIN
 CORROSION - CATEGORY 1B. SERIOUS EYE DAMAGE - CATEGORY 1. SPECIFIC
 TARGET ORGAN TOXICITY - SINGLE EXPOSURE - CATEGORY 3 RESPIRATORY
 SYSTEM. CARCINOGENICITY — CATEGORY 1B.

SIGNAL WORD..... DANGER.

HAZARD STATEMENT..... H226 FLAMMABLE LIQUID AND VAPOUR. H290 MAY BE CORROSIVE TO METALS.
 H314 CAUSES SEVERE SKIN BURNS AND EYE DAMAGE. H318 CAUSES SERIOUS
 EYE DAMAGE. H302 HARMFUL IF SWALLOWED. H272 MAY INTENSIFY FIRE;
 OXIDIZER. H335 MAY CAUSE RESPIRATORY IRRITATION. H350 MAY CAUSE
 CANCER THROUGH PROLONGED OR REPEATED EXPOSURE.

PRECAUTIONARY STATEMENT..... P210 KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT SURFACES. – NO
 SMOKING. P233 KEEP CONTAINER TIGHTLY CLOSED. P240 GROUND/BOND
 CONTAINER AND RECEIVING EQUIPMENT. P241 USE EXPLOSION-PROOF
 ELECTRICAL/VENTILATING/LIGHTING/EQUIPMENT. P242 USE ONLY
 NON-SPARKING TOOLS. P280 WEAR PROTECTIVE GLOVES/PROTECTIVE
 CLOTHING/EYE PROTECTION/FACE PROTECTION. P303+P361+P353 IF ON SKIN
 (OR HAIR): REMOVE/TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING.
 RINSE SKIN WITH WATER/SHOWER. P403+P235 STORE IN A WELL-VENTILATED
 PLACE. KEEP COOL. P405 STORE LOCKED UP. P501 DISPOSE OF
 CONTENTS/CONTAINER TO APPROPRIATE WASTE SITE OR RECLAIMER IN
 ACCORDANCE WITH LOCAL AND NATIONAL REGULATIONS. P234 KEEP ONLY IN
 ORIGINAL CONTAINER. P390 ABSORB SPILLAGE TO PREVENT MATERIAL DAMAGE.
 P406 STORE IN CORROSIVE RESISTANT CONTAINER WITH A RESISTANT INNER
 LINER. P260 DO NOT BREATHE DUST/FUME/GAS/MIST/VAPOURS/SPRAY. P264
 WASH SKIN THOROUGHLY AFTER HANDLING. P301+P330+P331 IF SWALLOWED:
 RINSE MOUTH. DO NOT INDUCE VOMITING. P363 WASH CONTAMINATED
 CLOTHING BEFORE REUSE. P304+P340+P310 IF INHALED: REMOVE VICTIM TO
 FRESH AIR AND KEEP AT REST IN A POSITION COMFORTABLE FOR BREATHING.
 IMMEDIATELY CALL A POISON CENTER OR DOCTOR/PHYSICIAN. P321 SPECIFIC
 TREATMENT (SEE SUPPLEMENTAL FIRST AID INSTRUCTIONS ON THE SAFETY
 DATA SHEET). P305+P351+P338+P310 IF IN EYES: RINSE CAUTIOUSLY WITH
 WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND
 EASY TO DO. CONTINUE RINSING. IMMEDIATELY CALL A POISON CENTER OR
 DOCTOR/PHYSICIAN. P270 DO NOT EAT, DRINK OR SMOKE WHEN USING THIS
 PRODUCT. P301+P312+P330 IF SWALLOWED: CALL A POISON CENTER OR
 DOCTOR/PHYSICIAN IF YOU FEEL UNWELL. RINSE MOUTH. P220 KEEP/STORE
 AWAY FROM CLOTHING/COMBUSTIBLE MATERIALS. P221 TAKE ANY PRECAUTION
 TO AVOID MIXING WITH COMBUSTIBLES.... P370+P378 IN CASE OF FIRE: USE DRY
 SAND, DRY CHEMICAL OR ALCOHOL-RESISTANT FOAM FOR EXTINCTION. P261
 AVOID BREATHING DUST/FUME/GAS/MIST/VAPOURS/SPRAY. P271 USE ONLY

PRODUCT: VINYL PLUS

CODE: MUR0017

SECTION 02: HAZARD IDENTIFICATION

PRECAUTIONARY STATEMENT..... OUTDOORS OR IN A WELL-VENTILATED AREA. P312 CALL A POISON CENTER OR DOCTOR/PHYSICIAN IF YOU FEEL UNWELL. P403+P233 STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED. P201 OBTAIN SPECIAL INSTRUCTIONS BEFORE USE. P202 DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD. P308+P313 IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE/ATTENTION.

OTHER HAZARDS..... NONE.

SECTION 03: COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS	CAS #	WT. %
DISODIUM METASILICATE	6834-92-0	8
GLYCOL ETHER DB	112-34-5	~5
NONYLPHENOL ETHOXYLATE	9016-45-9	1-2
TETRASODIUM ETHYLENEDIAMINE TETRAACETATE TETRAHYDRATE	13235-36-4	<1
ALKYL DIMETHYL BENZYL AMMONIUM CHLORIDE	53516-76-0	<1
ALKYL(C12-14) DIMETHYL(ETHYLBENZYL) AMMONIUM CHLORIDE	85409-23-0	<1
SODIUM NITRITE	7632-00-0	<1

SECTION 04: FIRST AID MEASURES

DESCRIPTION OF FIRST AID MEASURES:

EYE CONTACT..... IN CASE OF CONTACT, OR SUSPECTED CONTACT, IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION IMMEDIATELY AFTER FLUSHING.

SKIN CONTACT..... IN CASE OF CONTACT, IMMEDIATELY FLUSH SKIN WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE.

INHALATION..... REMOVE PERSON TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GET IMMEDIATE MEDICAL ATTENTION.

INGESTION..... DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS OR CONVULSING PERSON. SEEK IMMEDIATE MEDICAL ATTENTION. IF VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO THE LUNGS.

MOST IMPORTANT SYMPTOMS AND SEE SECTION 11.
EFFECTS, ACUTE OR DELAYED:

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED NOTES TO PHYSICIAN: TREATMENT BASED ON SOUND JUDGMENT OF PHYSICIAN AND INDIVIDUAL REACTIONS OF PATIENT.

SECTION 05: FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA..... USE DRY CHEMICALS, CO2, ALCOHOL FOAM OR WATER SPRAY.
UNSUITABLE EXTINGUISHING MEDIA..... N.AV.

SPECIAL HAZARDS ARISING FROM THE PRODUCT: ISOLATE AND RESTRICT AREA ACCESS. USE WATER SPRAY TO COOL FIRE-EXPOSED CONTAINERS AND STRUCTURES. FIGHT FIRE FROM A SAFE DISTANCE AND FROM A PROTECTED LOCATION. DO NOT DIRECT A SOLID STREAM OF WATER OR FOAM INTO HOT, BURNING POOLS; THIS MAY CAUSE FROTHING AND INCREASE FIRE INTENSITY. THIS MATERIAL MAY PRODUCE A FLOATING FIRE HAZARD IN EXTREME FIRE CONDITIONS. CONTAINER MAY RUPTURE FROM GAS GENERATION IN A FIRE SITUATION.

HAZARDOUS COMBUSTION PRODUCTS. CARBON DIOXIDE, CARBON MONOXIDE. TOXIC FUMES. ACRID SMOKE AND IRRITATING FUMES. OXIDES OF NITROGEN.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS: FIRE FIGHTERS SHOULD WEAR FULL PROTECTIVE CLOTHING, INCLUDING SELF-CONTAINED BREATHING EQUIPMENT.

SECTION 06: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS..... KEEP UNNECESSARY PERSONNEL AWAY. KEEP PEOPLE AWAY FROM AND UPWIND OF SPILL/LEAK. ELIMINATE ALL IGNITION SOURCES (NO SMOKING, FLARES, SPARKS, OR FLAMES IN IMMEDIATE AREA). WEAR APPROPRIATE

PRODUCT: VINYL PLUS

CODE: MUR0017

SECTION 06: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS..... PROTECTIVE EQUIPMENT AND CLOTHING DURING CLEAN-UP. DO NOT BREATHE MIST OR VAPOR. DO NOT TOUCH DAMAGED CONTAINERS OR SPILLED MATERIAL UNLESS WEARING APPROPRIATE PROTECTIVE CLOTHING. VENTILATE CLOSED SPACES BEFORE ENTERING THEM. LOCAL AUTHORITIES SHOULD BE ADVISED IF SIGNIFICANT SPILLAGES CANNOT BE CONTAINED. FOR PERSONAL PROTECTION, SEE SECTION 8 OF THE SDS.

ENVIRONMENTAL PRECAUTIONS..... AVOID RELEASE TO THE ENVIRONMENT. PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. AVOID DISCHARGE INTO DRAINS, WATER COURSES OR ONTO THE GROUND. INFORM APPROPRIATE MANAGERIAL OR SUPERVISORY PERSONNEL OF ALL ENVIRONMENTAL RELEASES. USE APPROPRIATE CONTAINMENT TO AVOID ENVIRONMENTAL CONTAMINATION.

METHODS AND MATERIALS FOR ISOLATE SPILL AND STOP LEAK WHERE SAFE. ABSORB WITH AN INERT DRY CONTAINMENT AND CLEANING UP MATERIAL AND PLACE IN AN APPROPRIATE WASTE DISPOSAL CONTAINER.

SECTION 07: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING:..... AVOID CONTACT WITH EYES, SKIN AND CLOTHING. AVOID BREATHING IN DUST. KEEP THE CONTAINERS CLOSED WHEN NOT IN USE. WASH THOROUGHLY AFTER HANDLING.

CONDITIONS FOR SAFE STORAGE, KEEP CONTAINERS TIGHTLY CLOSED. STORE IN CLEAN, TIGHTLY CLOSED STEEL INCLUDING ANY IMCOMPATIBILITIES: CONTAINERS. PLACE AWAY FROM INCOMPATIBLE MATERIAL. DO NOT STORE IN ALUMINUM, FIBERGLASS, COPPER, BRASS, ZINC OR GALVANIZED CONTAINERS. STORE IN COOL, DRY AND WELL VENTILATED LOCATION. STORE LOCKED UP.

SECTION 08: EXPOSURE CONTROLS AND PERSONAL PROTECTION

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
DISODIUM METASILICATE	N.AV.	N.AV.	N.AV.	N.AV.	N.AV.	N.AV.
GLYCOL ETHER DB	N.AV.	N.AV.	N.AV.	N.AV.	N.AV.	N.AV.
NONYLPHENOL ETHOXYLATE	N.AV.	N.AV.	N.AV.	N.AV.	N.AV.	N.AV.
TETRASODIUM ETHYLENEDIAMINE TETRAACETATE TETRAHYDRATE	N.AV.	N.AV.	N.AV.	N.AV.	N.AV.	N.AV.
ALKYL DIMETHYL BENZYL AMMONIUM CHLORIDE	N.AV.	N.AV.	N.AV.	N.AV.	N.AV.	N.AV.
ALKYL(C12-14) DIMETHYL(ETHYLBENZYL) AMMONIUM CHLORIDE	N.AV.	N.AV.	N.AV.	N.AV.	N.AV.	N.AV.
SODIUM NITRITE	N.AV.	N.AV.	N.AV.	N.AV.	N.AV.	N.AV.
APPROPRIATE ENGINEERING CONTROLS	GENERAL VENTILATION. LOCAL EXHAUST VENTILATION AS NECESSARY TO MAINTAIN EXPOSURES TO WITHIN APPLICABLE LIMITS.					
INDIVIDUAL PROTECTION MEASURE SUCH AS PERSONAL PROTECTIVE EQUIPMENTS:						
HAND PROTECTION.....	WEAR IMPERVIOUS CHEMICAL RESISTANT GLOVES.					
RESPIRATORY PROTECTION.....	IF MIST OR VAPOUR FORMATION SHOULD OCCUR, USE A NIOSH APPROVED RESPIRATOR.					
EYE PROTECTION.....	CHEMICAL GOGGLES AND/OR FACE SHIELDS SHOULD BE WORN WHERE SPLASHING IS A POSSIBILITY.					
PROTECTIVE CLOTHING.....	APRON, COVERALLS AND/OR OTHER RESISTANT PROTECTIVE CLOTHING. IMPERVIOUS CLOTHING.					
PROTECTIVE FOOTWEAR.....	WEAR CHEMICAL-RESISTANT FOOTWEAR.					
OTHER.....	EYEWASH STATION AND SAFETY SHOWER IN WORK AREA.					
HYGIENIC PRACTICES.....	USE GOOD PERSONAL HYGIENE PRACTICES. WASH HANDS BEFORE EATING, DRINKING, OR SMOKING, OR USING TOILET FACILITIES. PROMPTLY REMOVE CONTAMINATED CLOTHING AND WASH THOROUGHLY BEFORE REUSE.					

PRODUCT: VINYL PLUS

CODE: MUR0017

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE..... LIQUID. LIGHT BLUE.
 COLOR..... LIGHT BLUE.
 ODOUR..... SLIGHT SWEET.
 ODOUR THRESHOLD..... N.AV.
 PH..... 12.2.
 FREEZING/MELTING POINT..... N.AV.
 BOILING POINT..... N.AV.
 FLASH POINT (C), METHOD..... N.AV.
 EVAPORATION RATE..... N.AV.
 FLAMMABILITY (SOLIDS AND GASES)..... N.AV.
 UPPER FLAMMABLE LIMIT (% BY VOL.)... N.AV.
 LOWER FLAMMABLE LIMIT (% BY VOL.)... N.AV.
 VAPOUR PRESSURE (MMHG)..... N.AV.
 VAPOUR DENSITY (AIR=1)..... N.AV.
 RELATIVE DENSITY..... 1.03.
 SOLUBILITY IN WATER (% W/W)..... SOLUBLE.
 COEFFICIENT OF WATER/OIL DIST..... N.AV.
 AUTO IGNITION TEMPERATURE..... N.AV.
 DECOMPOSITION TEMPERATURE..... N.AV.
 VISCOSITY..... N.AV.

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY:..... STABLE UNDER NORMAL CONDITIONS.
 CHEMICAL STABILITY:..... STABLE UNDER RECOMMENDED HANDLING AND STORAGE CONDITIONS.
 POSSIBILITY OF HAZARDOUS REACTIONS:..... HAZARDOUS POLYMERIZATION WILL NOT OCCUR.
 CONDITIONS TO AVOID..... CONTACT WITH INCOMPATIBLES. PRODUCT CAN OXIDIZE AT ELEVATED TEMPERATURES. GENERATION OF GAS DURING DECOMPOSITION CAN CAUSE PRESSURE IN CLOSED SYSTEMS.
 INCOMPATIBLE MATERIALS:..... CONTACT WITH ACIDS. GENERATES HEAT WHEN MIXED WITH ACID. MAY REACT WITH AMMONIUM SALT SOLUTIONS RESULTING IN EVOLUTION OF AMMONIA GAS. FLAMMABLE HYDROGEN GAS MAY BE PRODUCED ON CONTACT WITH ALUMINUM, TIN, LEAD, AND ZINC. CARBON MONOXIDE GAS MAY BE PRODUCED ON CONTACT WITH REDUCING SUGARS. STRONG OXIDIZING AGENTS, STRONG BASES. ALKALIS. ORGANIC MATTER. COMBUSTIBLE MATERIAL. REDUCING AGENTS. THIOSULFATES. THIOCYANATES. AMMONIUM COMPOUNDS.
 HAZARDOUS PRODUCTS OF DECOMPOSITION..... CARBON OXIDE, CARBON DIOXIDE. HYDROGEN GAS. AMMONIA. OXIDES OF NITROGEN. IRRITATING VAPORS. TOXIC FUMES.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
DISODIUM METASILICATE	N.AV.	1153 MG/KG (ORAL, RAT); 770 MG/KG (ORAL, MOUSE)
GLYCOL ETHER DB	N.AV.	3384 MG/KG (ORAL, RAT);) 2700 MG/KG (DERMAL, RABBIT)
NONYLPHENOL ETHOXYLATE	N.AV.	1310 MG/KG (ORAL, RAT); >50 G/KG (ORAL, MOUSE); 2 ML/KG (DERMAL, RABBIT)
TETRASODIUM ETHYLENEDIAMINE TETRAACETATE TETRAHYDRATE	N.AV.	N.AV.
ALKYL DIMETHYL BENZYL AMMONIUM CHLORIDE	N.AV.	3560 MG/KG (DERMAL); 430 MG/KG (ORAL)
ALKYL(C12-14) DIMETHYL(ETHYLBENZYL) AMMONIUM CHLORIDE	N.AV.	3560 MG/KG (DERMAL); 430 MG/KG (ORAL)
SODIUM NITRITE	5.5 MG/L 4 H (INH, RAT)	85 MG/KG (ORAL, RAT)

INFORMATION ON LIKELY ROUTES OF ENTRY:

SKIN CONTACT..... CORROSIVE. CAUSES BURNS.
 SKIN ABSORPTION..... N.AV.
 EYE CONTACT..... CORROSIVE. CAUSES EYE BURNS.
 INHALATION..... CORROSIVE TO THE RESPIRATORY PASSAGE.
 INGESTION..... CORROSIVE. CAUSES BURNS TO THE MOUTH, THROAT AND STOMACH.
 EFFECTS OF ACUTE EXPOSURE..... SEE ABOVE.

PRODUCT: VINYL PLUS

CODE: MUR0017

SECTION 11: TOXICOLOGICAL INFORMATION

EFFECTS OF CHRONIC EXPOSURE..... SUBCHRONIC DATA: IN A STUDY OF RATS FED SODIUM SILICATE IN DRINKING WATER FOR THREE MONTHS, AT 200, 600 AND 1800 PPM, CHANGES WERE REPORTED IN THE BLOOD CHEMISTRY OF SOME ANIMALS, BUT NO SPECIFIC CHANGES TO THE ORGANS OF THE ANIMALS DUE TO SODIUM SILICATE ADMINISTRATION WERE OBSERVED IN ANY OF THE DOSAGE GROUPS. ANOTHER STUDY REPORTED ADVERSE EFFECTS TO THE KIDNEYS OF DOGS FED SODIUM SILICATE IN THEIR DIET AT 2.4G/KG/DAY FOR 4 WEEKS, WHEREAS RATS FED THE SAME DOSAGE DID NOT DEVELOP ANY TREATMENT-RELATED EFFECTS. DECREASED NUMBERS OF BIRTHS AND SURVIVAL TO WEANING WAS REPORTED FOR RATS FED SODIUM SILICATE IN THEIR DRINKING WATER AT 600 AND 1200 PPM.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

CARCINOGENICITY OF MATERIAL..... SODIUM NITRITE: IARC – 2A PROBABLY CARCINOGENIC TO HUMANS (NITRATE OR NITRITE (INGESTED) UNDER CONDITIONS THAT RESULT IN ENDOGENOUS NITROSATION).

TERATOGENICITY..... N.AV.
 MUTAGENICITY..... N.AV.
 REPRODUCTIVE EFFECTS..... N.AV.
 SENSITIZING CAPABILITY OF MATERIAL..... N.AV.
 SYNERGISTIC MATERIALS..... N.AV.

SECTION 12: ECOLOGICAL CONSIDERATIONS

ECOTOXICITY..... N.AV.
 PERSISTENCE AND DEGRADATION..... N.AV.
 BIOACCUMULATIVE POTENTIAL..... N.AV.
 MOBILITY IN SOIL..... N.AV.
 OTHER ADVERSE EFFECTS..... N.AV.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS:..... DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS.

SECTION 14: TRANSPORT INFORMATION

UN NUMBER..... 1760.
 PROPER SHIPPING NAME..... CORROSIVE LIQUIDS, N.O.S. (DISODIUM TRIOXOSILICATE).
 TDG CLASSIFICATION..... 8.
 PACKING GROUP..... III.
 ENVIRONMENTAL HAZARDS ACCORDING TO THE INTERNATIONAL MARITIME DANGEROUS GOODS CODE AND THE UNITED NATIONS MODEL REGULATIONS: N.AV.
 SPECIAL PRECAUTIONS IN CONNECTION WITH TRANSPORT OR CONVEYANCE EITHER WITHIN OR OUTSIDE THE PREMISES: N.AV.

SECTION 15: REGULATORY INFORMATION

SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS SPECIFIC TO THE PRODUCT: N.AV.

SECTION 16: OTHER INFORMATION

N.AV.=NOT AVAILABLE
 N.AP.=NOT APPLICABLE
 OTHER INFORMATION.....

THE DATA IN THIS MSDS RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED HEREIN AND DOES NOT RELATE TO USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY PROCESS. THIS DATA IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS PRODUCT SPECIFICATIONS. NO WARRANTY, EITHER EXPRESSED OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE AND DETERMINE WHETHER THEY ARE APPROPRIATE.

PREPARED BY..... REGULATORY AFFAIRS
 PREPARATION DATE..... APR 18/2017